

## 120 BBL Vac Trailer - Spec and Non-Spec Options

- Length** 42' Overall length
- Barrel** Single compartment, 16#/gallon max product weight, 200 degrees Fahrenheit max tem, 14.5 PSI
- Shell/Heads** .250 carbon steel mill finish top shell. Heads D & F .250 carbon steel mill finish
- Baffles** (2) baffles, dished with straight flange
- Manholes** (3) 20" full opening on top
- Frame** Bolster saddle style with welded rails at subframes
- Ladder/Walkway** Non-skid stairway at rear driver side with handrails. Full width walkway galvanized steel on driver side. 3/4" handrail along outside of walkway.
- Kingpin Plate** Heavy duty bolt on 4" increments, 2" adjustments
- Landing Gear** 2-speed with sand shoes, curbside crank
- Nosebox** 7-way ATA connector and trailer gladhand connectors at
- Lights** Bells 12V LED. Right light box two lights per. Document holder on landing leg subframe, roadside, (2) work lights at rear top. On/Off switch at ground level.
- Hose Trough** (2) 5" full length with drains at rear. One mounted each side
- Outlet** (1) 6" x 90 degree outlet at bottom rear head with 6" butterfly valve and NPT flange.



## Fully Self-Contained Units

- Load Line** 4" load line at rear extending into top interior with 4" butterfly valve and NPT flange
- Primary Shutoff** In front 20" manway, 3" port and 8" stainless steel float ball
- Secondary** 10 gallon moisture trap w/3" NPT thread ports
- Bleeder Line** 3" steel Bleeder line with 3" valve with rear linkage handle control
- Gauges/Floats** Rotary ball float type gauge with level indicator at rear head left side
- Venting** 1 1/2" pressure/vacuum relief valves at front top of trailer