

21,000 Gallon Capacity Potable Water Storage Tank

- Operating Specs** Max Pressure Rating 1 PSI/Max Vacuum Rating 0.25 PSI
- Side Wall** 1/4" A36 Steel Plate
- Floor** 1/4" A36 Steel Plate
- Roof** 1/4" A36 Steel Plate
- Main Rails** Structural Channel - 12" x 3" x 20.7 pounds/foot
- Manways** (3) 20" Manways, located front, top, and rear; (1) 25" Curb Side Manway; Equipped with Buna-N Gaskets
- Relief Valve** Blaylock Pressure/Vacuum Valve, Model LL10 - 16oz/in Pressure; 0.4oz/in Vacuum
- Metering Gauge** (2) 8" Stainless Steel Float Balls
- Drain/Fill Valves** 4" Butterfly Valves Front and Rear
- Fill Line** 3" Sch 40 Fill Line w/Cap Located Front & Rear
- Gel Line** 4" Gel Line with Butterfly Valve
- Manifold** Cold weather tank interior manifold or exterior 8" manifold available
- Suspension** Spring - 22.5K Capacity
- Axle** 5" RD; 77.5" Track
- Wheels & Tires** 8.25 x 22.5 Steel Wheels w/11R22.5 - 14ply Tires

Length 45' 6" (546 Inches)

Height 11' (133 inches) from the ground

Width 8' 5" (102 inches)

Capacity 21,000 Gallons (500.9 bbl)

Lights DOT Approved Lights

Blast Interior - SSPC-SP10

Exterior - SSPC-SP6

Interior Paint Carboline Epoxy Coated 25-30mm

Exterior Paint Carboline Coated with Carbothane 8845



Potable Water Tanks