

## 18,900 Gallon/450 BBL Tank with Integrated Berm

- Length** 44' (528 inches)
- Height** 8' 5" (101 inches)
- Width** 8' 9" (105 inches)
- Capacity** 18,900 Gallons (450 bbl)
- Floor Plate** 1/4" A36 Plate, 1/4" Double V-Floor
- Front Sheet** 3/16" A36 Plate
- Side Sheet** 3/16" A36 Plate
- Rear Sheet** 3/16" A36 Plate
- Main Floor Rails** 12" x 20.7# Structural Channel
- Side Stakes** Tubing 6" x 2" x 1/4"
- Suspension** 3 Leaf Spring, 22,500 lbs. Capacity
  - Axle** 77.5" Track, 22,500 lbs. Capacity
  - Tires** 11R 22.5 Radial
- Wheels** 8.25 x 22.5 Steel
- Manways** 2 - 20" Diameter (Roof)
- Fitted Connections** 2 - 4" Flanged Connections (Front)  
4 - 3" Bulkhead Connections (Roof)
- Vent** Blaylock Pressure Relief Valve



- Constructed with High Density XLPE
- Steel Cage with Roll-Off Understructure
- Front Stairs with Platform
- Rear Ladder
- Rotomolded for Seamless Construction
- OR-1000 for added Resistance / Durability
- Hydro-Tested Against Leakage
- Dual IMFO Outlets for Full Drainage