

## 12,600 Gallon/300 BBL Poly Tank

**Length** 44' (528 inches)

**Height** 8' 5" (101 inches)

**Width** 8' 9" (105 inches)

**Capacity** 12,600 Gallons (300 bbl)

**Floor Plate** 1/4" A36 Plate

**Front Sheet** 3/16" A36 Plate

**Side Sheet** 3/16" A36 Plate

**Rear Sheet** 3/16" A36 Plate

**Main Floor Rails** 12" x 20.7# Structural Channel

**Side Stakes** Tubing 6" x 2" x 1/4"

**Suspension** 3 Leaf Spring, 22,500 lbs. Capacity

**Axle** 77.5" Track, 22,500 lbs. Capacity

**Tires** 11R22.5 Radial

**Wheels** 8.25 x 22.5 Steel

**Manways** 2 - 24" Diameter (Roof)

**Fitted Connections** 2 - 4" Flanged Connections (Front)

4 - 3" Bulkhead Connections (Roof)

**Vent** Blaylock Pressure Relief Valve



- Constructed with High Density XLPE
- Steel Cage with Roll-Off Understructure
- Front Stairs with Platform
- Rear Ladder
- Rotomolded for Seamless Construction
- OR-1000 for added Resistance / Durability